

Do you value your time? Does your work demand high quality output? Do you need to share access of laser printers over a network? If you've answered yes to any of the previous questions, then the Elite 21N from GCC Printers is the perfect choice for your laser printing needs. The Elite 21N prints 21 pages per minute at a crisp 1200 x 1200 dpi resolution. It's powered by a fast PowerPC processor and has a 650-sheet standard input capacity (with the ability to support up to two additional 550-sheet paper feeders). Quality output, faster printing and less wasted time refilling paper trays! But there's more - the Elite 21N ships with 10/100 BaseT Ethernet so it's network ready out of the box. No hidden costs to incur getting your Elite 21N connected to the network!

The Elite 21N, what more could you ask for in a printer?

10/100 BaseT Ethernet

Parallel

USB

Serial

**Network-ready
straight from the box**

**Super-fast
PowerPC processor**



Features

**PowerPC 403
GCX Processor**

**1200 x 1200
Addressable Resolution**

**Enhanced Connectivity
Options**

**PostScript® Level 2,
PCL® 6, Type 1 and
TrueType Compatible**

Expanded Font Set

**Exceptional Paper
Handling**

**Advanced Paper Tray
Technology**

**Custom Paper Size
Option**

WebAdmin™

Memory Upgrades

Transmit-once Collation

Flash ROM

Benefits

Rapidly processes your complex documents – reducing down time!

Produces clear, crisp documents and images with any size typeface.

Network-ready out of the box - 10/100 BaseT Ethernet connection allows for easy networking. Plus, USB connectivity for Macintosh® and Windows® 98/2000.

Ensures compatibility with both Macintosh and Windows platforms.

136 resident PostScript 3 compatible/80 PCL fonts come standard with the printer.

Designed to support up to 1750 sheets of paper with optional paper trays. More work is completed without having to reload paper trays.

Includes a motorized paper feeder with 550-sheet universal tray that holds an entire ream of paper! And a visual paper level indicator so that keeping an eye on your paper supply is quick and easy!

Allows printing to the exact specifications of your media.

Provides remote access to printer interface settings, network protocol parameters, printer status, paper handling capabilities and more from your computer.

As your needs expand the standard 16 MB configuration can be expanded up to 256 MB, using industry standard 72-pin SIMMS.

Enjoy the luxury of multiple original prints without tying up your computer or the network. Your job is sent to the printer just once, no matter how many copies you select to print.

High-speed synchronous flash assures you always have the most current software features.

Specifications

Print Engine	Fuji-Xerox (P752)
Print Method	Dry-type electrographic printing
Print Engine Speed	21 ppm 7.5 ppm @ duplex speed
Resolution	1200 x 1200 dots per inch (600/1200 dpi software selectable)
Printer Languages	PostScript Level 2 & PCL 6 (5e/XL) compatible, HP-GL/2
Connectivity	Ethernet (10/100 BaseT) Universal Serial Bus (Win 98/2000 & Mac only), ECP Bi-directional Parallel, RS-232 Serial
Network Compatibility	EtherTalk®, NetWare® (IPX/SPX), TCP/IP
Supported Platforms	Mac OS 7, 8, 9, OS X, Windows 95/98/2000/ME/NT 4.0, NetWare, UNIX
Fonts Included	136 PostScript 3 compatible/80 PCL
Paper Trays/Capacity	
Standard:	Motorized Paper Feeder (includes 550-sheet Universal Tray) (Letter/A4, Legal) Multi-purpose Tray (100 sheets or 10 envelopes)
Optional:	Additional Paper Feeder(s) (includes 550-sheet Replacement Tray) 75-sheet Motorized Envelope Feeder 500-sheet Upper Output Bin Internal Duplex Unit
Paper Types	Cut sheets (16-36 lbs.), labels, envelopes, overhead transparency film, postcards
Printable Area	8.33" x 13.83"/212 mm x 352 mm
Toner	Single-piece cartridge 15,000 letter pages at 5% black (single-sided)
Memory	16 MB RAM, expandable to 256 MB
Controller	PowerPC 403 GCX processor @ 80 MHz
Power	100/115 VAC, 50/60 Hz (North America) 220/240 VAC, 50/60 Hz (Europe)
Dimensions (H x D x W)	16.3" x 17.3" x 16.6" (413 x 439 x 422 mm)
Weight	59.3 lbs. (26.9 kgs.) (Unpackaged - including toner & universal tray)
Noise Level	
Operational:	53.0 dB max.
Standby:	35.0 dB max.

www.gccprinters.com

United States 209 Burlington Road, Bedford, MA 01730

Tel: 800.422.7777 Fax: 781.275.1115

Australia 9 Burramine Road, Glen Waverley 3150, Melbourne, VIC

Tel: +61 1 800 422 832 Fax: +61 1 300 361 829

Germany Vertriebsbüro Deutschland, Hahnbuschweg 2-4, D-24147 Klausdorf bei Kiel

Tel: +49 431 7997610 Fax: +49 431 7997666

United Kingdom 729 London Road, Hounslow, Middlesex TW3 1SE

Tel: +44 208 754 6000 Fax: +44 208 754 6060